

# fence & deck cleaner liquid

by NOOP'S COUP®



## WOOD BRIGHTENER

### BENEFITS:

- Safer, faster, easier
- Non-flammable
- Non-caustic
- User and environmentally friendly
- Removes streaks and stains
- Neutralizes mold and mildew
- Lowers pH in wood
- Restores natural patina of wood
- Great final wash for stripped wood

**PRODUCT DESCRIPTION:** FENCE & DECK CLEANER by NOOP'S COUP® is a non-chlorine dry bleach product designed to wash wooden fences, decks, concrete walks, driveways and roofs. It kills mildew and the molds stachybotrys and aspergillus. It will help to kill microorganisms over time. It removes streaks and stains while restoring the natural patina of wood. It neutralizes mold and mildew, and lowers the pH in wood. It lightens and brightens fences, decks and roofs. Although this product contains oxalic acid, it has a different combination of chemicals that works just as good as if not better than any other product on the market.

**RECOMMENDED APPLICATION:** Always cover plants and shrubs. Mix 1 cup FENCE & DECK CLEANER by NOOP'S COUP® with 4 gallons warm water. Stir to mix. If wood is really dark, worn or stained, mix 2 dry cups cleaner with 4 gallons warm water. Wet surface to be washed thoroughly. If surface to be cleaned is vertical, use brush or spray bottle to apply from bottom up. If surface to be cleaned is horizontal, brush mixture over entire area. Scrub with hard bristle brush. Spots or streaks? Reapply and scrub again. Wash off thoroughly with water. Rinse shrubs with a fine mist of water. Wait 24 hours for product to dry before refinishing or painting. For heavy mold or mildew areas, after initial cleaning, apply double strength dose of cleaner to area and let dry. Do not rinse off.

**COST CONFIGURATION:** Cost varies depending upon application and size of area to be cleaned. Approximately **20 gallons of cleaner can be made from 1 pound dry mix.**

**TECHNICAL SERVICES:** Someone is normally available to answer questions regarding products in use. We have over 30 years of experience in paint removal. Our removers and cleaners REALLY WORK! All products are tested in our stripping plant, so we know what your problems are. Normal hours are 8:00 AM - 5:00 PM ET, Monday to Friday.

## READ AND FOLLOW ALL INSTRUCTIONS & SAFETY PRECAUTIONS BEFORE USING THIS PRODUCT.

### RECOMMENDED FOR USE ON MOST:

Wood, concrete walks, driveways and roofs.

### PERSONAL SAFETY:

THIS PRODUCT DOES BURN SKIN. But as with all chemicals, excessive use or overexposure may irritate or dry out skin.

- Face:** Dust mask and safety goggles when handling product.
- Gloves:** Neoprene, Viton, PVC coated.
- Other Equipment:** Long sleeves and pants if splashing is a problem.

### EMERGENCY & FIRST AID:

- Eyes:** Flush thoroughly with water for 15 minutes. If irritation persists, seek medical attention.
- Skin:** Wash with soap and water.
- Inhalation:** Move to fresh air. Give artificial respiration and medical attention if necessary.
- Clothing:** Wash before reuse.

### TECHNICAL DATA:

- Color:** Colorless to White
- Flash Point:** None
- Vapor Pressure:** N/A
- Solubility:** [% in Water] Complete

**SIZES AVAILABLE:** 1 Quart, 1 Gallon, 5 Gallon

### SEE MATERIAL SAFETY DATA SHEET FOR USE, PERSONAL SAFETY & DISPOSAL PROCEDURES.

### SEE WEBSITE FOR MORE INFORMATION.

**WARRANTY:** NOOP'S COUP® Products are warranted against manufacturing defects and to perform as advertised and instructed on package. Use and application of the product must conform to product instructions. NOOP'S COUP® shall not, under any circumstances, be liable for any consequential or any other damages in connection with your use of this product. Liability for product shall not exceed replacement cost. (Product warranty & liability information is available from manufacturer.)



**Specialists in Removers That Really Work!**

Manufactured by:  
**NOOP'S COUP®, LLC**

**Main Office:**  
108 Route 40  
Newfield, NJ 08344  
**856-358-6001**  
Fax: 856-358-0206

**Sales Office:**  
145 West Ruby Avenue  
Palisades Park, NJ 07650  
**201-840-9300**  
Fax: 201-840-9301

**Technical Information:**  
**856-404-0338**