

graffiti away4

by NOOP'S COUP®

BENEFITS:

- Faster
- Easier
- Super heavy duty
- Less labor
- Environmentally friendly
- Multiple applications
- Biodegradable for unpainted masonry
- Specifically designed to work in temperatures of 40°F to 65°F in conjunction with warm or hot water and a high pressure (2000+ psi) power washer

PRODUCT DESCRIPTION: GRAFFITI AWAY 4 by NOOP'S COUP® removes graffiti from both porous and smooth surfaces. Graffiti is removed from large areas because it can be applied with a paint brush, roller, Hudson sprayer or an airless sprayer. Wash off with a power washer or hose with nozzle, and decrease your labor costs for spray applications. EXCELLENT FOR USE BY: Commercial and contractors, schools, bridges, city & county parks and highway departments, trains, buses, etc.

RECOMMENDED APPLICATION: Test a small area first to determine how long it will take to do job. Stir thoroughly before and during use. Apply remover - can be moved in any direction. Allow to work for 15-20 minutes. Scrape or scrub surface. Always scrub away from yourself. Wash off with power washer with hot or warm water. Always spray away from yourself. If necessary, re-apply.

COST CONFIGURATION: Cost varies depending upon application and type of graffiti to be removed. Average coverage is 30 sq. ft. to 50 sq. ft. per gallon.

TECHNICAL SERVICES: Someone is normally available to answer questions regarding products in use. We have over 30 years of experience in paint removal. Our removers and cleaners REALLY WORK! All products are tested in our stripping plant, so we know what your problems are. Normal hours are 8:00 AM - 5:00 PM ET, Monday to Friday.

RECOMMENDED FOR USE ON MOST: Brick, concrete, wood, marble, glazed brick, terrazzo, porcelain tile, stainless steel, steel, cinder block, rocks, slate, stucco, ceramic tile, aluminum, and many more metals.

RECOMMENDED TEMPERATURES: 40°F - 65°F
Some very hard to remove industrial coatings will require additional time to work.

READ AND FOLLOW ALL INSTRUCTIONS & SAFETY PRECAUTIONS BEFORE USING THIS PRODUCT.

LIMITATIONS: The effectiveness of this product is decreased when temperatures are below freezing, or when it rains. DO NOT use this product on pre-painted surfaces unless you want them stripped. DO NOT use on asphalt, rubber, plastic tile, linoleum or carpet.

PERSONAL SAFETY: THIS PRODUCT WILL BURN THE SKIN. Wearing protective gloves, long sleeved shirts, long pants, safety goggles for your eyes or a face shield to cover your face is highly recommended.

EMERGENCY & FIRST AID:

Eyes: Flush thoroughly with water for 15 minutes. If irritation persists, seek medical attention.
Skin: Wash with soap and water.
Inhalation: Move to fresh air.
Clothing: Wash before re-use.

TECHNICAL DATA:

Color: Dark Brown Liquid
Weight per Gallon: 8 lbs
Boiling Point: 359°F
Flash Point: None to Boiling
Vapor Pressure: (mmHg) @ 20°C = Water
Solubility: (% in Water) Complete
VOC Vapor Pressure: (mmHg) @ 20°C = AP 0.3

SIZES AVAILABLE: 1 Quart, 1 Gallon, 5 Gallon

SEE MATERIAL SAFETY DATA SHEET FOR USE, PERSONAL SAFETY & DISPOSAL PROCEDURES.

Go to www.noopscoup.com for more information.

WARRANTY: NOOP'S COUP® Products are warranted against manufacturing defects and to perform as advertised and instructed on package. Use and application of the product must conform to product instructions. NOOP'S COUP® shall not, under any circumstances, be liable for any consequential or any other damages in connection with your use of this product. Liability for product shall not exceed replacement cost. (Product warranty & liability information is available from manufacturer.)



Manufactured by:
NOOP'S COUP®, LLC

Main Office:
108 Route 40
Newfield, NJ 08344
856-358-6001
Fax: 856-358-0206

Sales Office:
145 West Ruby Avenue
Palisades Park, NJ 07650
201-840-9300
Fax: 201-840-9301

Technical Information:
856-404-0338

www.noopscoup.com