

graffiti away¹

by NOOP'S COUP[®]



BENEFITS:

- Safer, faster, easier
- Super heavy duty
- Anti-bacterial
- Non-flammable & non-caustic
- User and environmentally friendly
- Biodegradable

PRODUCT DESCRIPTION: GRAFFITI AWAY 1 by NOOP'S COUP[®] is specially designed to remove graffiti and overspray from factory baked on painted surfaces such as cars and trucks.

EXCELLENT FOR USE BY: Commercial and industrial contractors, schools, city & county maintenance departments, trains, buses, airplanes and other public transportation vehicles, highways and thruways, bridges, etc.

RECOMMENDED APPLICATION: Test a small area first. Pour product onto a cloth and rub until the graffiti or overspray is removed. Wash off with water and a clean cloth. If necessary, re-apply. Stripped area may seem duller than surrounding area. Rewaxing surfaces may be necessary.

COST CONFIGURATION: Cost varies depending upon application and type of graffiti to be removed. Average coverage is 30 sq. ft. to 50 sq. ft. per gallon.

TECHNICAL SERVICES: Someone is normally available to answer questions regarding products in use. We have over 30 years of experience in paint removal. Our removers and cleaners REALLY WORK! All products are tested in our stripping plant, so we know what your problems are. Normal hours are 8:00 AM - 5:00 PM ET, Monday to Friday.

REMOVES MOST: Spray paints, overspray, ink, tar, grease, grime, gum, magic marker, bugs, nail polish, dry latex paint and adhesive tape residue, etc.

FROM MOST: Cars, trucks, boats, fiberglass, bricks, street signs, concrete, marble, slate, glazed brick, terrazzo, porcelain & ceramic tile, stucco, public rest room walls, gym lockers, school playground equipment, cinderblocks, other metals and many more surfaces.

LIMITATIONS: Some plexiglass or plastics may stain, scar or cloud. Always test an inconspicuous area first. DO NOT strip in direct, hot sunlight. DO NOT strip on cold, damp, rainy days. DO NOT use on asphalt, rubber, linoleum or plastiv tile. Test carpet before use.

READ AND FOLLOW ALL INSTRUCTIONS & SAFETY PRECAUTIONS BEFORE USING THIS PRODUCT.

RECOMMENDED TEMPERATURES: 60°F - 100°F

Under 60°F: Use a heat lamp from 3 ft away to warm surface. Product will not work effectively on freezing or cold, damp rainy days.

PERSONAL SAFETY: THIS PRODUCT DOES NOT BURN THE SKIN. But as with all chemicals, excessive use or overexposure may irritate or dry out skin. Use of long sleeved shirts, rubber gloves and safety goggles for your eyes are recommended.

EMERGENCY & FIRST AID:

Eyes: Flush thoroughly with water for 15 minutes. If irritation persists, seek medical attention.

Skin: Wash with soap and water.

Inhalation: Move to fresh air.

Clothing: Wash before re-use.

TECHNICAL DATA:

Color: Dark Green Liquid

Weight per Gallon: 8 lbs

Boiling Point: 310°F

Flash Point: None to Boiling

Vapor Pressure: (mmHg) @ 20°C <1

Solubility: (% in Water) Complete

VOC Vapor Pressure: (mmHg) @ 20°C = AP 0.3

SIZES AVAILABLE: 1 Quart, 1 Gallon, 5 Gallon

SEE MATERIAL SAFETY DATA SHEET FOR USE, PERSONAL SAFETY & DISPOSAL PROCEDURES.

Go to www.noopscoup.com for more information.

WARRANTY: NOOP'S COUP[®] Products are warranted against manufacturing defects and to perform as advertised and instructed on package. Use and application of the product must conform to product instructions. NOOP'S COUP[®] shall not, under any circumstances, be liable for any consequential or any other damages in connection with your use of this product. Liability for product shall not exceed replacement cost. (Product warranty & liability information is available from manufacturer.)



**Specialists in Removers
That Really Work!**

Manufactured by:
NOOP'S COUP^{®,} LLC

Main Office:
108 Route 40
Newfield, NJ 08344
856-358-6001
Fax: 856-358-0206

Sales Office:
145 West Ruby Avenue
Palisades Park, NJ 07650
201-840-9300
Fax: 201-840-9301

Technical Information:
856-404-0338

www.noopscoup.com