

MATERIAL SAFETY DATA SHEET

Prepared according to CFR 29 1910, 372
Effective: 01/01/2008

Product Identification:

Label Away Remover
Softens Glue/Adhesives for Easy Removal

SECTION 1 A - MANUFACTURER'S IDENTIFICATION

NOOP'S COUP[®], LLC
108 Route 40
Newfield, NJ 08344

Emergency Phone: 1-800-424-9300
Main Office: 1-856-358-6001
Fax Number: 1-856-358-0206

SECTION 1 B - PRODUCT INFORMATION

Trade Name: NOOP'S COUP[®] Label Away Green Line
Type/Usage: Softens Glues & Adhesives for Easy Removal
DOT Shipping Name: Mixture, Combustible & Flammable Liquid

SECTION II - CHEMICAL/Common Name

N-Methyl Pyrrolidone
Soybean Oil
D'Limonene

HAZARD

100 (estimate)
100
N/A

% BY WEIGHT

100
100
N/A

CAS#

872-50-4
67784-80-9
5989-27-5

SECTION III - HAZARDS IDENTIFICATION: Health - 1 Flammability - 3 Reactivity - 0

Eye Contact: Causes moderate irritation.
Skin Contact: Causes moderate irritation.
Inhalation: Prolonged use may cause dry skin or irritation.
Ingestion: May cause nose, throat or respiratory irritation. If swallowed, may be aspirated and cause lung damage.

SECTION IV - FIRST AID MEASURES

Eyes: Remove contacts at once. Flush with large amounts of water for 15 minutes.
Skin: Wash with soap and water. Wash clothing before reuse. If irritation persists, SEEK MEDICAL ATTENTION.
Inhalation: MOVE TO FRESH AIR. Administer artificial respiration if breathing is stopped.
Ingestion: Do not induce vomiting. Seek immediate medical attention. Keep at rest. SEEK MEDICAL ATTENTION.

SECTION V - FIRE FIGHTING MEASURES

Flash Point: 150°F (Closed Up)
Flammable Limits: **LFL:** 1.3% @ 25°C; **UFL:** 9.5% @ 25°C
Extinguishing Media: Use water fog, foam, dry chemical, or carbon dioxide (Co2) to extinguish flames.
Inappropriate Extinguishing Media: Straight streams of water.
Fire Fighting: Use water spray to cool fire exposed surfaces and to protect personnel. Prevent runoff from entering streams, sewers or drinking water supply. Firefighters should use standard protective equipment and self-contained breathing apparatus (SCBA) in close places. Vapors are heavier than air and may travel along the ground and reach remote.
Unusual Fire Hazards: Vapors are heavier than air and may travel along the ground and reach remote.
Decomposition Products under Fire Conditions: Oxides of carbon, smoke, fumes.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Ventilate area. Avoid breathing of vapors. Use self contained breathing apparatus or airmask for large spills in a confined area. Wipe or soak up in an inert material and put in a container for disposal. See **Section V** "unusual fire and explosion hazards" for proper procedures. Remove sources of ignition. Remove with inert absorbent and non-sparking tools. Avoid contact with eyes. Prevent entry into waterways, sewers or confined areas. Dispose of according to local, state and federal regulations.

SECTION VII - STORAGE & HANDLING

Store in a cool, ventilated area. DO NOT handle or store near open flame, heat or other sources of ignition. Do not store in direct sunlight. Avoid contact with eyes. Use with non-sparking tools. Use with adequate ventilation. Prevent small spills and leakage to avoid slip hazard.

SECTION VIII - EXPOSURE CONTROL/PERSONAL PROTECTION

Eye & Face Protection: Wear chemical resistant goggles and face shield if splashing is a problem.
Skin Protection: Chemical resistant gloves. Clothing to cover exposed areas.
Respiratory: Use with adequate ventilation. OSHA Permissible Exposure Limits (PEL) TWA 1000 mg/m3 (400 ppm)

SECTION IX - PHYSICAL & CHEMICAL PROPERTIES

Appearance:	Green Cast	Odor:	Slight Petroleum Odor
Vapor Pressure:	(mmHg) @ 20°C <1	Vapor Density:	(Air=1) 0.3
% Volatile by Volume:	0%	Solubility (% in Water):	Complete
Specific Gravity of Vapor:	(H2 0=1) @ 25 / 25°C	Evaporation Rate:	(Ether = 1) <1
Boiling Point:	359°F	VOC Vapro Pressure:	mm HG @ 20°C = AP 0.3
Weight per Gallon:	8 lbs		

SECTION X - STABILITY & REACTIVITY

Stability: Product is stable under normal conditions.
Hazardous Polymerization: Will not occur.
Conditions to Avoid: Heat, sparks, open flames & other ignition sources. Do not mix with other chemicals.

DISCLAIMER OF LIABILITY

The information in this MSDS was obtained from sources which we believe to be reliable. However, the information is provided without warranty, expressed or implied. We do not assume responsibility and expressly disclaim liability for loss, damage or expense rising out of, or in any way connected with the handling, storage, use or disposal of the product. This MSDS may not be applicable if the product is used as a component of another product.