

MATERIAL SAFETY DATA SHEET

Prepared according to CFR 1910 1200 372
Effective: 02/01/2006

Product Identification:

Vintage Automotive, Marine, Aircraft &
Multiple Layer Paint Remover

SECTION 1 A - MANUFACTURER'S IDENTIFICATION

NOOP'S COUP[®], LLC
108 Route 40
Newfield, NJ 08344

Emergency Phone: 1-800-424-9300
Main Office: 1-856-358-6001
Fax Number: 1-856-358-0206

SECTION 1 B - PRODUCT INFORMATION

Trade Name: NOOP'S COUP[®] Vintage Stripper[®]
Type/Usage: Automotive, Marine, Aircraft & Multiple Layer Paint Remover
DOT ID#: NA1993 Consumer Commodity - ORM-D
DOT Shipping Name: Mixture

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY

| CHEMICAL/Common Name | OSHA PEL (PPM) | ACGIH TLV (PPM) | CAS# | WEIGHT BY % |
|----------------------|----------------|-----------------|-----------|-------------|
| Methylene Chloride: | 500 TWA | 50 | 75-09-2 | 80 |
| Methanol Alcohol: | 200 TLV | 200 | 67-56-1 | 10 |
| Mineral Spirits: | 1000 | 1000 | 8052-41-3 | 5 |
| Additives: | | | | 5 |

SECTION III - PHYSICAL & CHEMICAL PROPERTIES

| | | | |
|-----------------------|-----------------------|--------------------------|-----------------|
| Appearance: | Faint Yellow Cast | Odor: | Almost Odorless |
| Vapor Pressure: | (mmHg) @ 20°C = 350 | Vapor Density: | 1.3 M SOLN |
| % Volatile by Volume: | 100 | Solubility (% in Water): | 2.0 g |
| VOC: | 194 g per Liter | VOC Vapor Pressure: | 12 mmHG @ 20°C |
| Specific Gravity: | (H2O=1) @ 25/25°C 1.2 | Boiling Point: | 104°F |
| Evaporation Rate: | (Ether=1) 0.7 | Weight per Gallon: | 10 lbs |

SECTION IV - FIRE FIGHTING MEASURES

| | |
|-----------------------------------|---|
| Flash Point: | None to Boiling (Tag Close Cup) |
| Flammable Limits: | LFL: 1.3% @ 25°C; UFL: 23% @ 225°C |
| Extinguishing Media: | Carbon dioxide, dry chemicals, water, fog, water spray to cool containers and avoid pressure build-up. |
| Unusual Fire Hazards: | This product is NON-FLAMMABLE, and NON-EXPLOSIVE at normal temperatures. At high temperatures, this product decomposes to hydrochloric acid as gas and other toxic vapors such as phosgene. If storage containers are exposed to excessive heat, over-pressurization of the container can result. |
| Special Fire Fighting Procedures: | Cool fire-exposed containers. Do not enter building without full protective equipment and NIOSH approved self-contained breathing apparatus. |

SECTION V - STABILITY & REACTIVITY

| | |
|-----------------------------------|--|
| Stability: | Product is stable under normal conditions. |
| Conditions to Avoid: | Pure oxygen, alkali metals, open flames electrical areas. Product may react with aluminum. |
| Hazardous Decomposition Products: | At high temperatures, this product may decompose to give off hydrogen chloride vapors, small quantities of phosgene, chlorine, carbon dioxide, carbon monoxide, and hydro-carbons. |
| Hazardous Polymerization: | Will not occur. |

SECTION VI - HEALTH HAZARDS

| | |
|---------------------------------------|--|
| Excessive Over-Exposure: | Brain damage, liver or kidney damage, nervous disorder. |
| Intentional Misuse: | Vomiting, nausea, fatigue, unconsciousness and even death in extreme cases. |
| Symptoms of Exposure: | Redness, tearing to eyes, respiratory and skin irritant, nausea, vomiting, diarrhea. |
| Carcinogenic: | NTP: Yes - Lists ethylene chloride as an animal carcinogen. LARC: Yes - Sufficient evidence of tumors in certain laboratory mice, and benign tumors in certain laboratory rats. Human studies have shown insufficient evidence. OSHA: No California: Yes - Proposition 65 lists methylene chloride as a chemical known to the state of California to cause cancer. |
| Routes of Entry: | Inhalation: Vomiting, nausea, drowsiness, nasal and respiratory irritation, fatigue, headaches, dizziness, unconsciousness and even death in extreme cases. Eyes: Contact will cause severe irritation, tearing, blurred vision, and pain. Skin: Contact will cause skin irritation or burning sensation. Pain or dermatitis may occur. Ingestion: Nausea, vomiting, diarrhea, intestinal irritation. Methylene chloride produces carbon monoxide in the body which reduces oxygen in the blood. |
| Emergency First Aid Procedures: | Eyes: Flush with water for 15 minutes. If symptoms persist, SEEK MEDICAL ATTENTION. Skin: Remove contaminated clothing, flush with large amounts of water. Neutralize with a 50/50 solution of white vinegar and water. If irritation persists, SEEK MEDICAL ATTENTION. Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give mouth to mouth. If symptoms persist, SEEK MEDICAL ATTENTION. Ingestion: If taken internally, drink large quantities of water or milk. DO NOT induce vomiting. SEEK MEDICAL ATTENTION. |
| Additional Information & Precautions: | This product contains METHYLENE CHLORIDE (UNI1593; CAS#75-09-2) which has been shown to cause cancer in certain laboratory animals. People who are pregnant , have allergies , or are suspected of having a heart condition should consult with their physician before using this product. The risk to your health depends upon concentration and duration of exposure. Work in a well ventilated area. Overexposure to this product can produce elevated carbonoxyhemoglobin levels. Never administer adrenaline. |
| Note to Physician: | |

Continued on next Page...